The Toaster XL is specially designed for a single application. It consists of processing two sleeves simultaneously

## **CHARACTERISTICS**

- Customized design
- 100% extruded aluminum structure.
- 100% Electric
- Extruded aluminum guard to prevent heat from building up and damaging equipment. Achieving a more efficient use of electrical energy and reducing heat loss.
- The equipment is designed to reduce the occupied space of the work area and is easily transportable within the plant.
- Thermocouple connectors for easy replacement.
- Complies with manufacturing 4.0.
- 2 working modes: manual and memory-based mode.
- USB and ethernet ports.
- Capacity of up to 20 memories.
- Backup mode for energy saving.
- Reader with scanner



## SPECIFICATIONS AND DIMENSIONS

Part number	XL2101
Electric	
Power Requirements	120VAC, 2500 Watts, 50/60 Hz
Heating chamber Big Actuator	1-Lower heater 120V, 500W 1-Upper heater thermocouple type k 120V, 500W
Heating chamber Small Actuator	1-Lower heater 120V, 500W 1-Upper heater thermocouple type k 120V, 500W
Time System	ProFace 1 to 999 seconds
Dimensions cm (in)	
Heating chamber Big Actuator	Length: 13 cm (5 in) x Width: 30 cm (12 in) x Height: 25 cm (10 in)
Heating chamber Small Actuator	Length: 15 cm (6 in) x Width: 28 cm (11 in) x Height: 28cm (11 in)
Control Box Dimensions	Length: 61 cm (24 in) x Width: 28 cm (11 in) x Height: 61 cm (24 in)
Machine Dimensions	Length: 135 cm (53 in) x Width: 84 cm (33 in) x Height: 145 cm (57 in)
Shipping Dimensions	Length: 165 cm (65 in) x Width: 97 cm (38 in) x Height: 165 cm (65 in)
Shipping Dimensions	Length: 213 cm (84 in) x Width: 86 cm (34 in) x Height: 157 cm (62 in)
Temperature	
Temperature control	Autonics temperature controller with a type K thermocouple on the upper heating elements.
Operating Temperature	0 ° C to 600 ° C maximum
Processing capacity	
Heating chamber Big Actuator	Up to 21 inches long up to 1 1/4 inch in diameter
Heating chamber Small Actuator	Up to 3 inch long and 1 ¼ inch in diameter





5.7 "touch screen independent of the control box for better use of the work area

1. Touch Screen





## 2. Process

Simultaneous processing of 2 heat sleeves with independent parameters

## 3. Tubing

It can process sleeves up to 120mm in length.